

TUPLES, LISTS, MUTABILITY

(download slides and .py files to follow along)

6.0001 LECTURE 5

Eric Grimson


LAST FEW LECTURES

- while loops & for loops
 - should know how to write both kinds
 - should know when to use them
 - computations characterized by “state variables” and update rules
- functions
- recursion
- decomposition and abstraction


TODAY

- new data types – tuples and lists
- mutable and immutable data structures
 - challenges of aliasing under mutation
- looping or recursing over compound data structures

Assigned Reading



- today:
 - section 5.1 – 5.5
- next lecture:
 - section 5.6
 - chapter 6
 - chapter 7



See <https://mitpress.mit.edu/books/introduction-computation-and-programming-using-python-second-edition> for errata sheet

A new data type



- Have seen scalar types: `int`, `float`, `bool`, `string`
- Want to introduce new **compound data types**
 - indexed sequences of elements, which could themselves be compound structures
 - tuples – immutable
 - lists – mutable
- Explore ideas of
 - Mutability
 - Aliasing
 - Cloning

TUPLES



- **Indexable ordered sequence** of objects
 - Objects can be any type – int, string, tuple, tuple of tuples, ...

Remember strings?

- Cannot change element values, **immutable**

```
te = ()
```

Empty tuple

```
ts = (2,)
```

Extra comma means tuple with one element

```
t = (2, "mit", 3)
```

Compare with ts = (2)

```
t[0]
```

→ evaluates to 2

Indexing starts at 0

```
(2, "mit", 3) + (5, 6) → evaluates to (2, "mit", 3, 5, 6)
```

```
t[1:2] → slice tuple, evaluates to ("mit",)
```

```
t[1:3] → slice tuple, evaluates to ("mit", 3)
```

```
len(t) → evaluates to 3
```

```
max((3, 5, 0)) → evaluates 5
```

```
t[1] = 4 → gives error, can't modify object
```

INDICES AND SLICING



```
seq = (2, 'a', 4, (1, 2))
```

index: 0 1 2 3

```
print(len(seq))      → 4
print(seq[3])        → (1, 2)
print(seq[-1])       → (1, 2)
print(seq[3][0])     → 1
print(seq[4])        → error
```

An element of a sequence is at an **index**, indices start at 0

```
print(seq[1])        → a
print(seq[-2:])      → (4, (1, 2))
print(seq[1:4:2])    → ('a', (1, 2))
print(seq[:-1])      → (2, 'a', 4)
print(seq[1:3])      → 'a', 4
```

Slices extract subsequences

```
for e in seq:
    print(e)
→ 2
  'a'
  4
  (1, 2)
```

Iterating over sequences

TUPLES



- Conveniently used to **swap** variable values

```
x = y
```

```
y = x
```



```
temp = x
```

```
x = y
```

```
y = temp
```



```
(x, y) = (y, x)
```



- Used to **return more than one value** from a function

```
def quotient_and_remainder(x, y):
```

```
    q = x // y
```

```
    r = x % y
```

```
    return (q, r)
```

```
(quot, rem) = quotient_and_remainder(4, 5)
```

```
both = quotient_and_remainder(4, 5)
```



KEEP
CALM
AND
TAKE YOUR
TURN ALREADY

YOUR TURN

Consider the following code:

```
def always_sunny(t1, t2):  
    """t1, t2 are non-empty"""  
    sun = ("sunny", "sun")  
    first = t1[0] + t2[0]  
    return (sun[0], first)
```

To what does `always_sunny(('cloudy'), ('cold',))` evaluate?

- A) ('sunny', 'cc')
- B) ('sunny', 'ccold')
- C) ('sunny', 'cloudycold')
- D) nothing, it will show an error

LISTS



- **Indexable ordered sequence** of objects
 - Usually homogeneous (i.e., all integers, all strings, all lists)
 - But can contain mixed types (not common)
- Denoted by **square brackets**, []
- **Mutable**, this means you can change element values

INDICES AND ORDERING



`a_list = []` *empty list*

`L = [2, 'a', 4, [1, 2]]`

`len(L)` → evaluates to 4

`L[0]` → evaluates to 2

`L[2]+1` → evaluates to 5

`L[3]` → evaluates to `[1, 2]`, another list!

`L[4]` → gives an error

`i = 2`

`L[i-1]` → evaluates to 'a' since `L[1] = 'a'`

`max([3, 5, 0])` → evaluates 5

MUTABILITY




- Lists are **mutable**!
- Assigning to an element at an index **changes** the value


```
L = [2, 1, 3]
```

```
L[1] = 5
```

- L is now [2, 5, 3]; note this is the **same object** L



*different from
strings and tuples!*



ITERATING OVER A LIST

- Compute the **sum of elements** of a list
- Common pattern

```
total = 0
for i in range(len(L)):
    total += L[i]
print(total)
```

```
total = 0
for i in L:
    total += i
print(total)
```

*Like strings, can
iterate over list
elements **directly***

*This version is
more "pythonic"!*

- Notice
 - List elements are indexed 0 to $\text{len}(L) - 1$
 - `range(n)` goes from 0 to $n - 1$



KEEP
CALM
AND
TAKE YOUR
TURN ALREADY

YOUR TURN

```
L= ["life", "answer", 42, 0]
```

```
for thing in L:  
    if thing == 0:  
        L[thing] = "universe"  
    elif thing == 42:  
        L[1] = "everything"
```

What is the value of L after you run this code?

- A) ["life", "answer", 42, 0]
- B) ["universe", "answer", 42, 0]
- C) ["universe", "everything", 42, 0]
- D) ["life", "everything", 42, 0]


OPERATION ON LISTS: append

- **Add** an element to end of list with `L.append(element)`

- **Mutates** the list!

```
L = [2, 1, 3]
```

```
L.append(5) → L is now [2, 1, 3, 5]
```




- What is the dot?
 - Lists are Python objects, everything in Python is an object
 - Objects have data
 - Objects have methods and functions
 - Access this information by `object_name.do_something()`
 - Equivalent to calling `append` with arguments `L` and `5`
 - Will learn more about these later

OPERATION ON LISTS – append

- **Add** an element to end of list with `L.append(element)`
- **Mutates** the list!

`L = [2, 1, 3]`

`L.append(5)` \rightarrow L is now `[2, 1, 3, 5]`




OPERATION ON LISTS – append

- **Add** an element to end of list with `L.append(element)`
- **Mutates** the list!

```
L = [2, 1, 3]
```

```
L.append(5) → L is now [2, 1, 3, 5]
```

```
L = L.append(5)
```




OPERATION ON LISTS – append

- **Add** an element to end of list with `L.append(element)`
- **Mutates** the list!

```
L = [2, 1, 3]
```

```
L.append(5) → L is now [2, 1, 3, 5]
```

```
L = L.append(5)
```




OPERATION ON LISTS – append

- **Add** an element to end of list with `L.append(element)`
- **Mutates** the list!

```
L = [2, 1, 3]
```

```
L.append(5) → L is now [2, 1, 3, 5]
```

```
L = L.append(5)
```



Be careful! The append operation does a mutation, but returns the None object as a result.

Append is used strictly for its side effect

TRICKY EXAMPLE 1: append

- **Range returns something that behaves like a tuple** (but isn't – it returns an *iterable*)
- Returns the first element, and an iteration method by which subsequent elements are generated as needed

`range(4)` → equivalent to tuple `(0, 1, 2, 3)`
`range(2, 6)` → equivalent to tuple `(2, 3, 4, 5)`

```
L = [1, 2, 3, 4]
```

```
for i in range(len(L))
```

```
    L.append(i)
```

```
    print(L)
```

• Iteration sequence is pre-determined at beginning of loop

0th time: L is [1, 2, 3, 4, 0]

1st time: L is [1, 2, 3, 4, 0, 1]

2nd time: L is [1, 2, 3, 4, 0, 1, 2]

3rd time: L is [1, 2, 3, 4, 0, 1, 2, 3]

TRICKY EXAMPLE 2: append

```
L = [1, 2, 3, 4]
```

```
i = 0
```

```
for e in L:
```

```
    L.append(i)
```


```
    i += 1
```

```
    print(L)
```

*L is mutated
each iteration*

*Originally
[1,2,3,4]*

In previous example, L was accessed at onset to create a range iterable; in this example, the loop is directly accessing indices into L



0th time: L is [1, 2, 3, 4, 0]

1st time: L is [1, 2, 3, 4, 0, 1]

2nd time: L is [1, 2, 3, 4, 0, 1, 2]

3rd time: L is [1, 2, 3, 4, 0, 1, 2, 3]

NEVER STOPS!

COMBINING LISTS

Remember strings

- **Concatenation**, + operator, creates a **new** list
- **Mutate** list with `L.extend(some_list)`

`L1 = [2, 1, 3]`


`L2 = [4, 5, 6]`

`L3 = L1 + L2`

→ L3 is `[2, 1, 3, 4, 5, 6]`

`L1.extend([0, 6])`

→ mutated L1 to `[2, 1, 3, 0, 6]`



Note that L3 does not change after we mutate L1, since it was created as a new list from the original L1

TRICKY EXAMPLE 3: combining

```
L = [1, 2, 3, 4] Originally [1,2,3,4]
```

```
for e in L:
```

```
    L = L + L
```

```
    print(L)
```

L is bound to a new object each iteration; but looping of e walks down structure pointed to when called, so iterates only 4 times, over original [1,2,3,4]

1st time: new L is [1, 2, 3, 4], [1, 2, 3, 4]

2nd time: new L is [1, 2, 3, 4, 1, 2, 3, 4],
[1, 2, 3, 4, 1, 2, 3, 4]

3rd time: new L is [1, 2, 3, 4, 1, 2, 3, 4,
1, 2, 3, 4, 1, 2, 3, 4,
1, 2, 3, 4, 1, 2, 3, 4,
1, 2, 3, 4, 1, 2, 3, 4]

4th time: new L is [1, 2, 3, 4, 1, 2, 3, 4,
1, 2, 3, 4, 1, 2, 3, 4,
1, 2, 3, 4, 1, 2, 3, 4,
1, 2, 3, 4, 1, 2, 3, 4,
1, 2, 3, 4, 1, 2, 3, 4]

[1, 2, 3, 4, 1, 2, 3, 4,
1, 2, 3, 4, 1, 2, 3, 4,
1, 2, 3, 4, 1, 2, 3, 4,
1, 2, 3, 4, 1, 2, 3, 4]

OPERATION ON LISTS: REMOVE

- Delete element at a **specific index** with `del (L[index])`
- Remove element at **end of list** with `L.pop()`, returns the removed element
- Remove a **specific element** with `L.remove(element)`
 - Looks for the element and removes it
 - If element occurs multiple times, removes first occurrence
 - If element not in list, gives an error

*all these
operations
mutate
the list*

```
L = [2, 1, 3, 6, 3, 7, 0] # do below in order
L.remove(2) → mutates L = [1, 3, 6, 3, 7, 0]
L.remove(3) → mutates L = [1, 6, 3, 7, 0]
del(L[1])   → mutates L = [1, 3, 7, 0]
L.pop()    → returns 0 and mutates L = [1, 3, 7]
```

MUTATION AND ITERATION

<http://www.pythontutor.com/> to see step-by-step

- **Avoid** mutating a list as you are iterating over it

```
def remove_dups(L1, L2):  
    for e in L1:  
        if e in L2:  
            L1.remove(e)
```



```
L1 = [1, 2, 3, 4]  
L2 = [1, 2, 5, 6]  
remove_dups(L1, L2)
```

```
def remove_dups(L1, L2):  
    L1_copy = L1[:]  
    for e in L1_copy:  
        if e in L2:  
            L1.remove(e)
```



- L1 is [2, 3, 4] not [3, 4] Why?

- Python uses an internal counter to keep track of index in the loop over list L1
- Mutating changes the list but Python doesn't update the counter
- Loop never sees element 2

*Clone list first
Note that L1_copy = L1
does NOT clone*

CONVERT LISTS TO STRINGS AND BACK

- Convert **string to list** with `list(s)`, returns a list with every character from `s` an element in `L`
- Can use `s.split()`, to **split a string on a character** parameter, splits on spaces if called without a parameter
- Use `' '.join(L)` to turn a **list of characters into a string**, can give a character in quotes to add char between every element

<code>s = "I<3 cs"</code>	→ <code>s</code> is a string
<code>list(s)</code>	→ returns <code>['I', '<', '3', ' ', 'c', 's']</code>
<code>s.split('<')</code>	→ returns <code>['I', '3 cs']</code>
<code>L = ['a', 'b', 'c']</code>	→ <code>L</code> is a list
<code>' '.join(L)</code>	→ returns <code>"abc"</code>
<code>'_'.join(L)</code>	→ returns <code>"a_b_c"</code>

OTHER LIST OPERATIONS



- `sort()` and `sorted()`
- `reverse()`

- and many more!

<https://docs.python.org/3/tutorial/datastructures.html>

```
L = [9, 6, 0, 3]
```

```
a = sorted(L) → returns sorted list, does not mutate L
```

```
a = L.sort() → mutates L = [0, 3, 6, 9], returns None
```

```
L.reverse() → mutates L = [9, 6, 3, 0]
```



KEEP
CALM
AND
TAKE YOUR
TURN ALREADY

YOUR TURN

```
L1 = ['re']
L2 = ['mi']
L3 = ['do']
L4 = L1 + L2
L3.extend(L4)
L3.sort()
del(L3[0])
L3.append(['fa', 'la'])
```

What is the value of L3 after you execute all the operations in this code?

- A) ['mi', 're', ['fa', 'la']]
- B) ['mi', 're', 'fa', 'la']
- C) ['re', 'mi', ['fa', 'la']]
- D) ['do', 'mi', ['fa', 'la']]

MUTATION, ALIASING, CLONING

IMPORTANT
and
TRICKY!

Again, Python Tutor is your best friend to help sort this out!

<http://www.pythontutor.com/>

LISTS IN MEMORY



- Lists are **mutable**
- Behave differently than immutable types
- A list is an object in memory
- Variable name points to object
- Using equal sign between mutable objects creates aliases
 - Both variables point to the same object in memory
- Any variable pointing to that object is affected by mutation of object
- Key phrase to keep in mind when working with lists is **side effects**

ALIASING



Boston
The Hub
Beantown

- City may be known by many names
- Attributes of a city
 - small, tech-savvy
- All nicknames point to the **same city**
 - add new attribute to **one nickname** ...

Boston

small

tech-savvy

snowy

... all the **aliases** refer to the old attribute and all the new ones

The Hub

small

tech-savvy

snowy

Beantown

small

tech-savvy

snowy


ALIASES




- `hot` is an **alias** for `warm` – changing one changes the other!
- `append()` has a side effect

Never explicitly changed warm, but structure has changed

```
1 a = 1
2 b = a
3 print(a)
4 print(b)
5
6 warm = ['red', 'yellow', 'orange']
7 hot = warm
8
9
10
```






CLONING A LIST

- Create a new list and **copy every element** using a clone

```
chill = cool[:]
```

```
1 cool = ['blue', 'green', 'grey']  
2  
3  
4  
5
```




SORTING LISTS




- Calling `sort()` **mutates** the list, returns `None`
- Calling `sorted()` **does not mutate** list, must assign result to a variable



```
1 warm = ['red', 'yellow', 'orange']
2
3
4
5
6
7
8
9
```




LISTS OF LISTS OF LISTS OF....



- Can have **nested** lists
- Side effects still possible after mutation



```
1 warm = ['yellow', 'orange']
2 hot = ['red']
3 brightcolors = [warm]
4 brightcolors.append(hot)
5 print(brightcolors)
6
7
8
```





KEEP
CALM
AND
TAKE YOUR
TURN ALREADY

YOUR TURN

```
L1 = ["bacon", "eggs"]  
L2 = ["toast", "jam"]  
brunch = L1  
L1.append("juice")  
brunch.extend(L2)
```

What is the value of `brunch` after you execute all the operations in this code?

- A) ["bacon", "eggs", "toast", "jam"]
- B) ["bacon", "eggs", "juice", "toast", "jam"]
- C) ["bacon", "eggs", "juice", ["toast", "jam"]]
- D) ["bacon", "eggs", ["toast", "jam"]]

LISTS ARE NATURALLY RECURSIVE



```
def total_iter(L):
```

```
    result = 0
```

```
    for e in L:
```

```
        result += len(e)
```

```
    return result
```

```
test = ["abc", 'd', "efghi"]
```

```
print(total_iter(test))
```

```
def total_recur(L):
```

```
    if L == []:
```

```
        return 0
```

```
    else:
```

```
        return len(L[0]) + \
```

```
            total_recur(L[1:])
```

```
test = ["abc", 'd', "efghi"]
```

```
print(total_recur(test))
```

LISTS ARE NATURALLY RECURSIVE



- The list operation `reverse` is built in; but we can easily see how a list naturally supports recursion
 - To reverse a list (as a copy), recursively reverse all but the first element, and add that element to the end




```
def my_rev(L):  
    if L == []:  
        return L  
    else:  
        return my_rev(L[1:]) + ([L[0]])
```

Note: concatenation expects a pair of lists

```
test2 = ["abc", ['d'], ['e', ['f', 'g']]]  
print(my_rev(test2))
```

CONTROL COPYING




- Assignment just creates a new pointer to same object

```
old_list = [[1,2],[3,4],[5,'foo']]  
new_list = old_list
```

```
new_list[2][1] = 6  
print("New list:", new_list)  
print("Old list:", old_list)
```

- So mutating one object changes the other



CONTROL COPYING

- Suppose we want to create a copy of a list, not just a shared pointer; shallow copying does this at the top level of the list

```
import copy
```

```
old_list = [[1,2],[3,4],[5,6]]
```

```
new_list = copy.copy(old_list)
```

```
print("New list:", new_list)
```


```
print("Old list:", old_list)
```

```
old_list = [[1,2],[3,4],[5,6]]
```

```
new_list = copy.copy(old_list)
```

```
print("New list:", new_list)
```

```
print("Old list:", old_list)
```



CONTROL COPYING

- Now we mutate the top level structure

```
import copy
```

```
old_list = [[1,2],[3,4],[5,6]]
```

```
new_list = copy.copy(old_list)
```

```
old_list.append([7,8])
```

```
print("New list:", new_list)
```


```
print("Old list:", old_list)
```

```
old_list = [[1,2],[3,4],[5,6]]  
new_list = copy.copy(old_list)
```

```
old_list.append([7,8])
```

```
print("New list:", new_list)
```

```
print("Old list:", old_list)
```



CONTROL COPYING

- But if we change an element in one of the sub-structures

```
import copy
old_list = [[1,2],[3,4],[5,6]]
new_list = copy.copy(old_list)

old_list.append([7,8])
old_list[1][1] = 9
print("New list:", new_list)
print("Old list:", old_list)
```


```
old_list = [[1,2],[3,4],[5,6]]
new_list = copy.copy(old_list)
```

```
old_list.append([7,8])
```

```
old_list[1][1] = 9
```

```
print("New list:", new_list)
```

```
print("Old list:", old_list)
```



CONTROL COPYING

- If we want all structures to be new copies, we need a deep copy

```
import copy
```

```
old_list = [[1,2],[3,4],[5,6]]
```

```
new_list = copy.deepcopy(old_list)
```

```
old_list.append([7,8])
```

```
old_list[1][1] = 9
```

```
print("New list:", new_list)
```

```
print("Old list:", old_list)
```


```
old_list = [[1,2],[3,4],[5,6]]
new_list = copy.deepcopy(old_list)
```

```
old_list.append([7,8])
```

```
old_list[1][1] = 9
```

```
print("New list:", new_list)
```

```
print("Old list:", old_list)
```



WRITING YOUR OWN VERSION




```
def my_deep_copy(L):  
    if L == []:  
        return L  
  
    elif type(L[0]) == type([]):  
        return ([my_deep_copy(L[0])] +\  
                my_deep_copy(L[1:]))  
  
    else:  
        return ([L[0]] + my_deep_copy(L[1:]))
```

WHY LISTS AND TUPLES?

- If mutation can cause so many problems, why do we even want to have lists, why not just use tuples?
 - Efficiency – if processing very large sequences, don't want to have to copy every time we change an element
- If lists basically do everything that tuples do, why not just have lists?
 - Immutable structures can be very valuable, e.g., we will see using immutable structures as keys into dictionaries next lecture

Take home message



- Lists and tuples provide compound data structures
 - Can be indexed
 - Can be sliced
- They naturally support recursive or iterative algorithms
- Many built in methods for processing lists – reverse, sort, sorted, append, extend, etc.
- Lists are mutable!
 - Need to be careful about aliasing – when two names refer to the same mutable structure